

GRAVITY-DEFYING BALANCERS

TW-SERIES BALANCERS

TW-0 and TW-00

- Gravity defying / "true balance".
- No tension buildup to cause worker fatigue.
- Easy external direct drive tensioning.
- 360 degree upper swivel.
- 3.3 ft stranded steel cable 1/8" diameter (TW-00 cable length 18").
- Safety cable provision.
- Tool clip included.



TW-0 & TW-00 Series

MODEL	CAPACITY		Anti-Gravity Capacity (lbs)
TW-00	1.1- 3.3 lb	0.5-1.5 kg	2.5-3.0
TW-0	1.1- 3.3 lb	0.5-1.5 kg	2.5-3.0
TW-3	2.2- 6.6 lb	1.0-3.0 kg	4.5-6.0
TW-5	5.5-11.0 lb	2.5-5.0 kg	8.0-10.5
TW-9	9.9-19.8 lb	4.5-9.0 kg	15.0-19.0
TW-15	19.8-33.0 lb	9.0-15.0 kg	26.0-32.5
TW-22	33.0-48.4 lb	15-22 kg	41.0-48.0
TW-30	48.4-66.0 lb	22-30 kg	58.0-65.5
TW-40	66.0-88.0 lb	30-40 kg	77.5-87.5
TW-50	88.0-110.0 lb	40-50 kg	100.0-109.5
TW-60	110.0-132.0 lb	50-60 kg	122.0-131.0
TW-70	132.0-154.0 lb	60-70 kg	144.0-153.0



TW-3 to TW-70 Series

TW-3 through TW-15

- Four (4) models supporting weights from 2.2 to 33 lb.
- Tapered drum allows "true balance" throughout cable travel.
- Easy external direct drive tensioning.
- Cast aluminum casing for durability.
- Permanent lubrication.
- 360 degree top swivel.
- 4.3 ft of 5/32" diameter stranded steel cable.
- Safety chain provision.
- Enclosed spiral spring for added safety.

TW-22 through TW-70

- Six (6) models supporting weights from 33 to 154 lb.
- Tapered drum allows for "true balance".
- Cast aluminum housing.
- Easy external tensioning.
- Manual drum lock.
- 360 degree upper swivel.
- Permanent lubrication.
- 5 ft of stranded steel 3/16".
- Automatic Safety Lock.
- Enclosed spiral spring for added safety.

ASB-SERIES BALANCERS

- Built-in Safety Features: The cable, drum, and enclosed spring are fully visible without opening the unit for easy and convenient safety checks. The sturdy spiral spring is enclosed for greater control and safety.
- Ergonomic Spring Release: The automatic safety lock provides extra control.
- Extended Cable Length: Stainless steel cables allow for extended reach on applications.
- Enhanced Gear Mechanism: Allows for more exact adjustment of tension.
- No Recoil and Low Resistance: Tapered drum style provides gravity defying tool positioning and low travel.

MODEL	CAPACITY		STROKE		WEIGHT	
ASB-0C	1.1 - 3.3 lb	0.5 - 1.5 kg	51.1 in	130 cm	1.5 lb	0.7 kg
ASB-3C	3.3 - 6.6 lb	1.5 - 3 kg	86.4 in	220 cm	3.0 lb	1.4 kg
ASB-5C	5.5 - 11 lb	2.5 - 5 kg	86.4 in	220 cm	3.4 lb	1.5 kg



ASB-OC Gravity Defying and Hand Adjustable Balancer



ASB-3C & ASB-5C

LINE REEL BALANCERS / RETRACTORS

LINE REEL BALANCERS

LR-Series

- Designed for light duty applications with small pneumatic tools.
- Integrating air hose and support cable keep work areas clean.
- Adjustable ball stop for optional positioning.
- 1/4" I.D. polyvinyl hose with 1/4" NPT inlet.
- 360 degree upper swivel.
- Maximum 142 PSI



MODEL	HOSE LENGTH		CAPACITY	
LR-09B-90	35.5 in	90 cm	3 lb	1.5 kg
LR-09B-200	78.3 in	199 cm	3 lb	1.5 kg

RETRACTORS

RPA Series

- No tools needed to set tension.
- 5 ft nylon coated steel cable.
- Reinforced hanging bracket includes safety cable provision.
- Adjustable cable stop.
- Three (3) models support weight 0.5-5 lb.
- Tool clip included.

RMA-L Series

- Steel housing with polyester finish.
- Reinforced hanging bracket includes safety cable provision.
- 8 ft of 3/32" diameter coated steel cable.
- Permanently lubricated.
- Tool clip included.
- External tension adjustment.
- Ratchet cable lock.



RMA-L Series



RPA Series

MODEL	CAPACITY	
RPA-1	0.5 - 1.5 lb	0.2 - 0.7 kg
RPA-2	1.5 - 3.0 lb	0.7 - 1.4 kg
RPA-3	3.0 - 5.0 lb	1.4 - 2.3 kg
RMA-7L	5 - 10 lb*	2.3 - 4.8 kg*
RMA-15L	10 - 15 lb*	4.5 - 6.8 kg*
RMA-20L	15 - 23 lb*	6.8 - 10.4 kg*

* With ratchet lock