

EY 7460 LZ2S

Cordless Drill & Driver

- High-performance 3.1Ah Li-ion battery pack
- 50min. usable and 60min. full charging
- Light weight 2.45kg (incl. battery)
- High performance with max. 63Nm
- 18-stage clutch plus drill position
- 13mm high-capacity drill chuck (keyless)
- Electric speed control
- Electric brake
- Reversible
- Compact body
- LED light
- Incl. second battery pack



MODEL / TYPE	EY 7460 LZ2S
Voltage	21.6V
Battery capacity accord. to IEC (technology)	3.1Ah (Li-ion)
Charging time (usable / full)	50 / 60min.
Speed at no load (low / high) in rpm	100 – 400 / 350 – 1,500
Max. torque (stalling / instant torque)	42 / 63Nm
Clutch torque	1.0 – 6.9Nm
Clutch stages	18 + drill position
Max. drilling diameter (in wood / in metal)	38 / 13mm
Max. holesaw size (in wood)	65mm
Size (W x L x B)	75 x 232 x 255mm
Weight (incl. battery)	2.45kg
Standard accessories (battery / charger / plastic box)	2 x battery EY 9L61 B
	EY 0L82 B
	incl. plastic box
Optional accessories	see page 52 – 53













Typical application

General construction, interior installation, electrical installation, assembly work in carpentry and locksmithery

LED light and symbols

LED light for working in dark areas. Flashing symbols point to low battery power and over-

NEW EY 74A1 LS2G / X

Cordless Drill & Driver

- New high-performance 4.2Ah Li-ion battery pack*
- 55min. usable and 70min. full charging
- Light weight 1.95kg (incl. battery)*
- High performance with max. 42Nm
- 18-stage clutch plus drill position
- 13mm high-capacity drill chuck (keyless)
- Electric speed control
- Electric brake
- Reversible
- Compact body
- LED light
- Incl. second battery pack*



Fig. EY 74A1 LS2G

MODEL / TYPE	EY 74A1 LS2G	EY 74A1 X
Voltage	18V	18V
Battery capacity accord. to IEC (technology)	4.2Ah (Li-ion)	*
Charging time (usable / full)	55 / 70min.	*
Speed at no load (low / high) in rpm	80 - 600 / 220 - 1,750	*
Max. torque (stalling / instant torque)	32 / 42Nm	*
Clutch torque	0.5 – 4.4Nm	*
Clutch stages	18 + drill position	*
Max. drilling diameter (in wood / in metal)	35 / 13mm	*
Max. holesaw size (in wood)	50mm	*
Size (W x L x B)	59 x 203 x 239mm	*
Weight (incl. battery)	1.95kg	*
Standard accessories (battery / charger / plastic box)	2 x battery EY 9L51 B	without
	EY 0L82 B	without
	incl. plastic box	without
Optional accessories	see page 52 – 53	
		.==.













Typical application

General construction, interior installation, electrical installation, assembly work in carpentry and locksmithery

Universally applicable

Powerful and durable with a compact design and weight of only 1.95kg (with 18V battery pack). You can even use the existing batteries from 14.4 / 18V Panasonic Li-ion units too.

EY 7450 LR2S / X

Cordless Drill & Driver

- High-performance 3.3Ah Li-ion battery pack*
- 40min. usable and 55min. full charging
- Light weight 2.15kg (incl. battery)*
- High performance with max. 57Nm
- 18-stage clutch plus drill position
- 13mm high-capacity drill chuck (keyless)
- Electric speed control
- Electric brake
- Reversible
- Compact body
- LED light
- Incl. second battery pack*



18V

MODEL / TYPE	EY 7450 LR2S	EY 7450 X
Voltage	18V	18V
Battery capacity accord. to IEC (technology)	3.3Ah (Li-ion)	*
Charging time (usable / full)	40 / 55min.	*
Speed at no load (low / high) in rpm	50 - 430 / 160 - 1,650	*
Max. torque (stalling / instant torque)	40 / 57Nm	*
Clutch torque	1.0 – 6.9Nm	*
Clutch stages	18 + drill position	*
Max. drilling diameter (in wood / in metal)	36 / 13mm	*
Max. holesaw size (in wood)	65mm	*
Size (W x L x B)	63 x 218 x 248mm	*
Weight (incl. battery)	2.15kg	*
Standard accessories (battery / charger / plastic box)	2 x battery EY 9L50 B	without
	EY 0L82 B	without
	incl. plastic box	without
Optional accessories	see page 52 – 53	







Typical application









carpentry and locksmithery 4-brush motor and controlling display

General construction, interior installation,

electrical installation, assembly work in

The new motor provides for highest performance in torque and speed stability. The control panel with LED light indicates temperature and battery status.

17

^{*} X-type (EY 74A1 X) without battery and charger.

^{*} X-type (EY 7450 X) without battery and charger.

4.2Ah 3.3 / 1.5Ah 14.4V

NEW EY 7443 LS2S / X

Cordless Auto Drill & Driver

- New high-performance 4.2Ah Li-ion battery pack*
- 50min. usable and 60min. full charging
- Light weight 1.85kg (incl. battery)*
- AUTO-function
- 18-stage clutch plus drill position
- 13mm high-capacity drill chuck (keyless)
- Electric speed control
- Electric brake
- Reversible
- Belt hook and soft grip
- LED light
- Incl. second battery pack*



MODEL / TYPE	EY 7443 LS2S	EY 7443 X
Voltage	14.4V	14.4V
Battery capacity accord. to IEC (technology)	4.2Ah (Li-ion)	*
Charging time (usable / full charging)	50 / 60min.	*
Speed at no load (low / auto, high) in rpm	60 - 400 / 160 - 1,400	*
Max. torque (stalling / instant torque)	28 / 41.5Nm	*
Clutch torque	0.5 – 4.4Nm	*
Clutch stages	18 + drill position	*
Max. drilling diameter (in wood / in metal)	35 / 13mm	*
Max. holesaw size (in metal)	33mm	*
Size (W x L x B)	62 x 199 x 254mm	*
Weight (incl. battery)	1.85kg	*
Standard accessories (battery / charger / plastic box)	2 x battery EY 9L45 B	without
	EY 0L82 B	without
	incl. plastic box	without
Optional accessories	see page 52 – 53	













Typical application

General construction, interior installation, electrical installation, assembly work in carpentry and locksmithery

Dynamic speed control

The EY 7443 offers three gear settings: HIGH, LOW and AUTO. Especially with long and difficult drillings, the AUTO mode always helps to find the best speed - totally automatically.

EY 7441 LR2S / LE2S / X

Cordless Drill & Driver

- High-performance 3.3Ah Li-ion battery pack*
- 55 / 35min. charging time (full charging)
- Light weight 1.75 / 1.5kg (incl. battery)*
- 18-stage clutch plus drill position
- 13mm high-capacity drill chuck (keyless)
- Electric speed control
- Flectric brake
- Reversible
- Belt hook and soft grip
- LED light
- Incl. second battery pack*



MODEL / TYPE	EY 7441 LR2S	EY 7441 LE2S	EY 7441 X
Voltage	14.4V	14.4V	14.4V
Battery capacity accord. to IEC (technology)	3.3Ah (Li-ion)	1.5Ah (Li-ion)	*
Charging time (usable / full charging)	40 / 55min.	30 / 35min.	*
Speed at no load (low / high) in rpm	70 - 400 / 200 - 1,400	70 - 400 / 200 - 1,400	*
Max. torque (stalling / instant torque)	28 / 41.5Nm	25.2 / 37.5Nm	*
Clutch torque	0.5 – 4.4Nm	0.5 – 4.4Nm	*
Clutch stages	18 + drill position	18 + drill position	*
Max. drilling diameter (in wood / in metal)	35 / 13mm	35 / 13mm	*
Max. holesaw size (in metal)	33mm	33mm	*
Size (W x L x B)	60 x 193 x 232mm	60 x 193 x 218mm	*
Weight (incl. battery)	1.75kg	1.5kg	*
Standard accessories (battery / charger / plastic box)	2 x battery EY 9L44 B	2 x battery EY 9L42 B	without
	EY 0L82 B	EY 0L82 B	without
	incl. plastic box	incl. plastic box	without
Optional accessories	see page 52 – 53	see page 52 – 53	



















Typical application

General construction, interior installation, electrical installation, assembly work in carpentry and locksmithery

For more Power

A constant torque is guaranteed by the electronic speed stabilisation at higher resistances. LED light for working in dark areas.

19

^{*} X-type (EY 7443 X) without battery and charger.

^{*} X-type (EY 7441 X) without battery and charger.