

NEW EY 75A1 LS2G / LR2F / X

Cordless Impact Driver

- New high-performance 4.2Ah Li-ion battery pack* available
- 55min. usable and 70min. full charging (18V)
- Light weight 1.65kg (incl. 18V battery)*
- 1/4" hex drive
- 3 speed/clutch stages (low / middle / high)
- Brushless motor and hybrid switch
- Electric speed control
- Electric brake
- Reversible
- Belt hook
- LED light
- Incl. second battery pack*



Fig. EY 75A1 LS2G

MODEL / TYPE	EY 75A1 LS2G	EY 75A1 LR2F	EY 75A1 X
Voltage	18V	14.4V	18 / 14.4V
Battery capacity accord. to IEC (technology)	4.2Ah (Li-ion)	3.3Ah (Li-ion)	*
Charging time (usable / full)	55 / 70min.	40 / 55min.	*
Max. torque (low / middle / high)	26 / 130 / 155Nm	26 / 130 / 150Nm	*
Speed at no load (low / middle / high) in rpm	0 - 1,000 0 - 1,400 0 - 2,500	0 - 1,000 0 - 1,400 0 - 2,500	*
Impact (low / middle / high) in rpm	0 - 2,000 0 - 2,800 0 - 3,000	0 - 2,000 0 - 2,800 0 - 3,000	*
Size (W x L x B)	61 x 143 x 242mm	61 x 143 x 233mm	*
Weight (incl. battery)	1.65kg	1.55kg	*
Standard accessories (battery / charger / plastic box)	2 x battery EY 9L51 B EY 0L82 B	2 x battery EY 9L44 B EY 0L82 B	without without
Optional accessories	incl. plastic box see page 52 - 53	incl. plastic box see page 52 - 53	without



70 min.



55 min.



Typical application

Air conditioning installation, repair and maintenance, general construction, decking

Compact and powerful

The new EY 75A1 offers power, versatility and durability. A variable impact rate [3 speed] gives you the power and control for virtually any screw-driving application. The slow start mode enables precise start to screwdriving without gliding off.

* X-type [EY 75A1 X] without battery and charger.

NEW EY 75A2 LS2G / LR2F / X

Cordless Impact Wrench

- New high-performance 4.2Ah Li-ion battery pack* available
- 55min. usable and 70min. full charging (18V)
- Light weight 1.65kg (incl. 18V battery)*
- 1/2" square drive
- Brushless motor
- Hybrid switch
- Electric speed control
- Electric brake
- Reversible
- Belt hook
- LED light
- Incl. second battery pack*



Fig. EY 75A2 LS2G

MODEL / TYPE	EY 75A2 LS2G	EY 75A2 LR2F	EY 75A2 X
Voltage	18V	14.4V	18 / 14.4V
Battery capacity accord. to IEC (technology)	4.2Ah (Li-ion)	3.3Ah (Li-ion)	*
Charging time (usable / full)	55 / 70min.	40 / 55min.	*
Max. torque (low / middle / high)	50 / 140 / 205Nm	50 / 140 / 200Nm	*
Speed at no load (low / middle / high) in rpm	0 - 1,000 0 - 1,400 0 - 2,300	0 - 1,000 0 - 1,400 0 - 2,300	*
Impact (low / middle / high) in rpm	0 - 2,000 0 - 2,800 0 - 3,500	0 - 2,000 0 - 2,800 0 - 3,500	*
Size (W x L x B)	61 x 155 x 242mm	61 x 155 x 233mm	*
Weight (incl. battery)	1.65kg	1.55kg	*
Standard accessories (battery / charger / plastic box)	2 x battery EY 9L51 B EY 0L82 B	2 x battery EY 9L44 B EY 0L82 B	without without
Optional accessories	incl. plastic box see page 52 - 53	incl. plastic box see page 52 - 53	without



70 min.



55 min.



Typical application

Air conditioning installation, automotive repair and maintenance, steel fabrication

Powerful support

With up to 205Nm of tightening torque the new EY 75A2 is ideal for almost all assembly applications. It features 3 impact speed settings which reduce or increase drive power. The ergonomic shape feels comfortable.

* X-type [EY 75A2 X] without battery and charger.