AccuBird[®]

AccuBird[®] – Reliability

- Electronic control
- No mechanical switching components
- Electronic temperature and overload protection
- High reliability through low loss power transmission via a highly efficient ball screw drive

AccuBird[®] – Freedom

Cablefree tool for flexible operation in installation jobs and industry production

AccuBird[®] – High performance

- High pulling force for safe setting of blind rivets up to 5 mm diameter in all materials
- High yield per battery charge
- Large 20mm stroke

AccuBird[®] – Versatility

Blind rivets up to 5 mm Ø all materials. BULB-TITE® blind rivets 4 mm; 5.2 and 6.3 mm Ø alu and steel



AccuBird[®] with battery 14.4 V / 1.3 Ah, and charger in carrying case **Part no. 725 0037**

AccuBird[®] with two batteries 14.4 V / 1.3 Ah, and charger in carrying case **Part no. 725 0019**

AccuBird[®] with battery 14.4 V / 1.3 Ah, and charger in cardboard box **Part no. 725 0029**

AccuBird[®] with battery 14.4 V / 1.3 Ah, in cardboard box **Part no. 725 0010**

AccuBird® with battery 14.4 V / 1.3 Ah, and charger with spring loaded trigger system in carrying case

Part no. 725 0015


GESIPA

AccuBird[®] – with Li-lon energy

Choice of 1.3 Ah and 2.6 Ah Li-lon batteries

AccuBird[®] – High speed

• High speed of operation through automatic resetting of the jaw mechanism immediately after each setting process



58

Rechargeable 14.4 Volt riveting tool with Li-lon battery

Working range

Sets blind rivets up to 5 mm Ø all materials. BULB-TITE® blind rivets 4 mm; 5.2 and 6.3 mm Ø alu and steel

Nosepieces / accessories

Nosepieces: 17/24, 17/27, 17/29 and 17/32

Technical data Weiaht: 2.0 kg with battery St

0	0 /
Stroke:	20 mm
Drive:	DC motor
Traction power:	10,000 N

Jaws (3 parts)

Part no. 725 1613

Nosepiece - power per battery charge

Blind rivet Ø in mm	Material	approx. pc/ battery charge	Nosepiece	Part no.
2.4	Alu	1,500	17/18*	725 2075
3.2	CAP-Alu, CAP-Cu	1,000	17/18*	725 2075
3 and 3.2	Alu	800	17/24	725 1583
3 and 3.2	Steel	800	17/24	725 1583
3 and 3.2	Stainless steel	800	17/24	725 1583
4	Alu	800	17/24	725 1583
4	Steel	700	17/27	725 2040
4	Stainless steel	640	17/29	725 2059
4.8 and 5	Alu	550	17/29	725 2059
4.8 and 5	Steel	420	17/32	725 2067
4.8 and 5	Stainless steel	320	17/36*	725 2083
6	Alu	240	17/36*	725 2083

Special nosepieces are available on request

BULB-TITE [◎] [⊪] lind rivet Ø in mm	Material	approx. pc/ battery charge	Nosepiece	Part no.
4	Alu	1,000	17/26 BT*	725 2202
5.2	Alu	800	17/32 BT*	725 2210
6.3	Alu	600	17/42 BT*	725 2229
6.3	Steel	300	17/42 BT*	725 2229

* Available as special accessory



Universal nosepiece - 17 To suit AccuBird®

Part no. 725 1637

Detailed information can be found on page 85

Special accessory: Retaining nosepiece

- Inserted rivet remains in any position
- Rivets may be set with only one hand
- Safer working

Retaining nose- piece	Part no.	Retaining nose- piece	Part no.
17/18 R	725 4078	17/29 R	725 4108
17/24 R	725 4086	17/32 R*	725 4116
17/27 R	725 4094	17/36 R*	725 4124

*also for PowerBird®

Federkraft

Changeover set (Part 50) for BULB-TITE® blind rivet: Part 54 (jaw pusher), Part 55 (jaws) and 3 nosepieces Part no. 725 9290

Charger 14.4 V Li-Ion

Part no. 725 1134



Technical data

Input voltage:	230 V / 50 Hz
Output voltage:	14.4 V DC
Recharging time:	50 to 100 minutes (battery depending)
Weight:	0.6 g

GESIF

Battery 14.4 V/1.3 Ah (Li-Ion) 14.4 V/2.6 Ah (Li-lon) Part no. 725 1045 Available as special accessory Weight: 0.35 g



Power battery

Part no. 725 1049

Weight: 0.5 g

Charger 12 V NiCd Part no. 725 1035

Extended spent mandrel container to suit AccuBird® and PowerBird® Part no. 725 9328



59

PowerBird[®]

PowerBird[®] – Innovation

As a stronger brother to the well-known AccuBird® the PowerBird® is the powerful extension of the so-called "Bird family" from GESIPA® able to cope with all high structure blind rivets.

PowerBird[®] – Practical aspects

• User oriented scope of delivery: metal carrying case with one battery charger, one battery and four nosepieces

PowerBird[®] – Economy

- Good price-performance ratio
- Large working range
- Short processing times
- High service life thanks to 2.6 Ah power battery

PowerBird[®] – With Li-Ion energy

2.6 Ah battery, alternatively 1.3 Ah on request



PowerBird[®] with power battery 14.4 Volt / 2.6 Ah and charger, in carrying case, **Part no. 724 0031**


PowerBird[®] with two power batteries 14.4 Volt / 2.6 Ah and charger, in carrying case, **Part no. 724 0040**

PowerBird® with power battery 14.4 Volt / 2.6 Ah and charger, in carrying case with spring loaded trigger system **Part no. 724 0160**



PowerBird[®] – Versatility

Blind rivets from 4.8 mm Ø steel, up to 6.4 mm Ø all materials and up to 8 mm alu, except G-Bulb® Ø 6.4 mm. Bulb-tite[®] blind rivets up to 7.7 mm Ø all materials. Mega Grip[®] blind rivets up to 6.4 mm Ø all materials.



GESIPA

60

Rechargeable 14.4 volt power battery riveting tool with Li-lon battery for even higher performance

Working range

Blind rivets from 4.8 mm Ø steel , up to 8 mm Ø alu and up to 6.4 mm all materials, except G-Bulb® Ø 6.4 mm. BULB-TITE® blind rivets up to 7.7 mm Ø all materials. MEGA GRIP® blind rivets up to 6.4 mm Ø all materials.

Technical data

Weight:	2.2kgwithbattery
Stroke:	20 mm
Drive:	DC motor
Traction power:	14,000 N

Nosepieces / accessories

es Jaws (3 parts)

Nosepieces: 17/32, 17/36, 17/40 and 17/45

Part no. 710 2208

Nosepiece - power per battery charge						
Rivet Ø	Rivet material approx. Nosepiece Part no.					
mm	pc/battery					
		charge				
4.8 and 5.0	Steel, Alu	700	17/32	725 2067		
4.8 and 5.0	Stainless steel	560	17/36	725 2083		
6.0	Alu	560	17/36	725 2083		
6.0	Steel	300	17/40	725 2560		
6.4	Alu, PG-Alu	420	17/45	724 3065		
6.4	Steel	250	17/45	724 3065		
8	Alu	350	17/45	724 3065		

BULB-TITE® blind rivet

4.0	Alu	1,000	17/26 BT*	725 2202
5.2	Alu	900	17/32 BT*	725 2210
6.3	Alu	590	17/42 BT*	725 2229
6.3	Steel	310	17/42 BT*	725 2229
6.3	Monel	380	17/42 BT*	725 2229
7.7	Alu	470	17/48 BT*	725 2237
			and jaws	715 1527

MEGA GRIP® blind rivet

4.8	Alu	600	17/31 MG*	725 2250
6.4	Alu	420	17/41 MG*	724 3146
4.8	Steel	420	17/31 MG*	725 2250
6.4	Steel	150	17/41 MG*	724 3146
4.8	Stainless steel	420	17/31 MG*	725 2250
6.4	Stainless steel	150	17/41 MG*	724 3146

* Available as special accessory Special design nosepieces are available on request



Special accessory: Retaining nosepiece

- Inserted rivet remains in any position
- Rivets may be set with only one hand



Retaining nosepiece	Part no.	Retaining nosepiece	Part no.
17/40 R	725 4125	17/45 R	725 4126

Charger 14.4 V Li-lon

Part no. 725 1134



Federkraft

Technical data

Input voltage: Output voltage: Recharging time: Weight:	230 V / 50 Hz 14.4 V DC 50 to 100 minutes (battery depending) 0.6 g
vveignt:	0.0 g

Battery 14.4 V/1.3 Ah (Li-Ion) Part no. 725 1045

Available as special accessory Weight: 0.35 g Power battery 14.4 V/2.6 Ah (Li-lon) Part no. 725 1049 Weight: 0.5 g

Charger 12 V NiCd Part no. 725 1035

One-piece, slim extension unit to approx. 110 mm, Ø 22.5 mm, for setting rivets in deep positions and with difficult access **Part no. 724 2054**

One-piece, slim extension unit to approx. 160 mm, Ø 22.5 mm, for setting rivets in deep positions and with difficult access **Part no. 724 2055**



PowerBird® Solar

Special design for solar applications Ideal for deep, difficult to access areas

Working range

Blind rivets from 4.8 mm Ø steel and up to 6.4 mm all materials, except G-Bulb® Ø 6.4 mm. BULB-TITE® blind rivets up to 7.7 mm Ø all materials. MEGA GRIP® blind rivets up to 6.4 mm Ø all materials.

Technical data

Weight: Stroke: Drive: Traction power: Extension unit: 2.36 kg with battery 20 mm DC motor 14,000 N approx. 160 mm

Nosepieces / accessories

approx. overall length160 mm extension two Li-lon power batteries 2.6 Ah/14.4 V Quick charger Nosepieces 17/32, 17/36, 17/40, 17/45, and 17/48 BT Plastic carrying c



Part no. 724 0041

Li-lon 14,4V 2.6Ah

GESIPA





The GESIPA® SolarGrip® blind rivet program can be found on page 30.

PowerBird® Gold Edition

The exclusive Gold Edition with 18,000 N traction power

Strong - stronger – PowerBird® Gold Edition

PowerBird[®], the all-rounder of the Bird family by GESIPA[®] with its wide range of application possibilities, is now available in an even stronger version: with a setting force of 18.000 N it can even set G-Bulb[®] and PolyGrip[®] blind rivets up to a diameter of 6.4 mm of all materials.

Practical - even more practical – PowerBird® Gold Edition

- Fatigue-free working through well balanced weight repartition and ergonomic grip
- Gravity controlled evacuation of spent mandrels: forward through the nosepiece or backwards into the mandrel container
- The immediate and automatic reset after each riveting process saves energy and speeds up the operation
- Exchange nosepieces and wrench always included in the tool eliminate work interruptions
- Compact, shockproof tool housing for all application conditions
- User oriented scope of delivery: plastic carrying case with one battery charger, one battery and four nosepieces (17/32, 17/36, 17/40, 17/45)

Nosepiece - power per battery charge

BULB-TITE®, PolyGrip®, G-Bulb® and standard blind rivet

Blind rivet Ø in mm	Material	approx. pc/battery charge	Nose- piece	Part no.
4.8 and 5.0	Steel, Alu	700	17/32	725 2067
4.8 and 5.0	Stainless steel, Stinox, PG- steel, PG stainless steel	560	17/36	725 2083
6.0	Alu	560	17/36	725 2083
6.0	Steel	300	17/40	725 2560
6.4	Alu	420	17/40	725 2560
6.4	Steel, PG-steel, Alu/alu, Stainless steel	250	17/45	724 3065
8	Alu	350	17/45	724 3065

G-Bulb® Blind rivet

4.8	Steel/steel	530	17/32	725 2067
6.4	Steel/steel	390	17/45	724 3065
4.8	Stainless steel/stainless steel	470	17/32	725 2067
6.4	Stainless steel/stainless steel	390	17/45	724 3065

MEGA GRIP® blind rivet

4.8	Alu	600	17/31 MG*	725 2250
6.4	Alu	420	17/41 MG*	724 3146
4.8	Steel	420	17/31 MG*	725 2250
6.4	Steel	150	17/41 MG*	724 3146
4.8	Stainless steel	420	17/31 MG*	724 2250
6.4	Stainless steel	150	17/41 MG*	724 3146

BULB-TITE® blind rivet

4.0	Alu	1,000	17/26 BT*	725 2202
5.2	Alu	900	17/32 BT*	725 2210
6.3	Alu	590	17/42 BT*	725 2229
6.3	Steel	310	17/42 BT*	725 2229
6.3	Monel/stainless steel	380	17/42 BT*	725 2229
7.7	Alu	470	17/48 BT*	725 2237
			and jaws*	715 1527

* Available as special accessory. Special design nosepieces are available on request



The all-round talent – PowerBird® Gold Edition

Processes blind rivets from \emptyset 4.8 mm steel to \emptyset 6.4 mm all materials, BULB-TITE® blind rivets up to \emptyset 7.7 mm, all materials, MEGA GRIP® blind rivets up to \emptyset 6.6 mm alu and steel, G-Bulb® blind rivets up to \emptyset 6.4 mm all materials, PolyGrip® blind rivet up to \emptyset 6.4 mm all materials.

PowerBird[®] Gold Edition – Technical data

Traction power: 18,000 Weight (incl. power battery): 2.2 kg Drive: DC motor Working stroke: 20 mm



PowerBird® Gold Edition

with power battery 14.4 Volt / 2.6 Ah and charger, in plastic carrying case, **Part no. 724 0001**

PowerBird[®] Gold Edition with spring loaded trigger system

with power battery 14.4 Volt / 2.6 Ah and charger, in plastic carrying case, **Part no. 724 0002**

Jaws (3 parts) for PowerBird® Gold Edition **Part no. 710 2208**

